

# SPECIFICATIONS FOR EL SERIES BODIES

Williamsen-Godwin's Crossmemberless design creates greater torsion resistance against twisting.

## LENGTH

10' to 20' long in 6" increments.

## WIDTH

84" I.D. 96" O.D.

Optional widths available upon request.

## HEIGHT

62" high front.

48" high sides.

48" high tailgate.

## SIDE & FRONT CONSTRUCTION

3/16" AR450 BHN 175/225K PSI quench and tempered, abrasion resistant steel with 25" radius to floor.

1/4" A656 boxed sloping top rail for maximum strength.

3/16" 50K rear corner posts, with holes for recessed lights.

## SIDE & FRONT OPTIONS

3/16" 50K steel.

1/8" or 1/4" AR450 BHN 175/225K PSI quench and tempered abrasion resistant steel.

## CYLINDER HOUSING

Outboard mounted cylinder standard  
Optional inboard mounted cylinder.

## UNDERSTRUCTURE

Torsion resistant design with 8" x 15" side flange I-beam stringers.

## UNDERSTRUCTURE OPTION

Trapezoidal 8" x 4" x 1/4" high tensile tubular stringers.

## FLOORS

3/16" AR450 BHN 175/225K PSI quench and tempered, abrasion resistant steel.

## FLOOR OPTIONS

1/4" AR450 BHN 175/225K PSI quench and tempered, abrasion resistant steel.

3/16" 50K high strength steel. 18" to 25" radius

## FENDERS

Sloping 10 gauge tread plate full length of the body.

## TAILGATE

Double paneled 3/16" AR450 steel with fully boxed parameter.

- Two integral formed horizontal braces.
- Straight tailgate with air operated hardware.
- Positive overlocking flame cut hardware.
- Recessed upper tailgate hinges.
- Double link hinges
- High lift double hinged tailgate, hydraulic or air operated, 15" additional clearance above corner post.

## TAILGATE OPTIONS

Inner panel made of 1/4" AR450 BHN 175/225K PSI quench and tempered, abrasion resistant steel.

- Sloping tailgate.
- Asphalt gates, lever actuated.
- Water tight tailgate.

## ADDITIONAL ELLIPTICAL BODY OPTIONS

- Stainless Steel Bodies
- Spreader aprons
- Walk rails
- Ladders
- Grip strut steps with grab handles
- Rubber cushion strips on stringers
- Asphalt rear end
- Cab protectors.

## LIGHTS

Recessed LED sealed system that complies with DOT and FMVSS108.

## COATINGS

Epoxy primed  
Urethane Top Coat  
Cured at 190°



**WILLIAMSEN • GODWIN**  
TRUCK BODY CO.

[www.williamsen-godwin.com](http://www.williamsen-godwin.com)

1.800.828.9847

1925 West Indiana Avenue • Salt Lake City, Utah 84104  
Phone (801) 973-9400 • Fax (801) 973-2838

**DISTRIBUTED BY:**

